

	DECLARATION OF DESIGN AND PERFORMANCE	Reference DDP 001720 2XX 00
	<i>Push pull connector type 1720</i>	Page 1 / 3

- **Name and address of supplier:** Amphenol Air LB
2, rue Clément Ader
ZAC de WE
08 110 CARIGNAN France

- **Description of product:** Push pull connectors in composite material.

- **Part number:**
 Plug for push pull connector with 26 male contacts ref: 001720 210 00;
 Plug for push pull connector with 10 male contacts ref: 001720 260 00;

 Receptacle for push pull connector with 26 female contacts ref: 001720 220 00;
 Receptacle for push pull connector with 10 female contacts ref: 001720 270 00;

 Cable clamp ref: 001720 232 00;

 Protective cover for receptacle ref: 001720 205 00.

- **Specification number:** ABS 0364

- **Overall dimensions, interfaces, connections (electrical, hydraulic, etc.), installation information in drawing:**
 According to Push pull connectors catalogue

- **Compliance statement related to the specification (including any limitations on use):**
 The qualification is equivalent to ABS 0364.

- **Inspection and maintenance instruction reference:** As specified in Amphenol Air LB quality manual

- **Qualification test report reference:** CRE 04-521 issue.ø

See following table for the main performances:

Constitution	
Shell material	Thermoplastic
Shell plating material	Not concerned
Insulation material	Silicone
Contact material	Not concerned
Contact plating material	Not concerned

Mechanical performances		
Description	Data	Units
Insert retention in housing (minimum)	35	daN
Contact retention in insert (minimum)	9	daN
Mechanical endurance	100	Cycles
Vibrations (type)	Sinusoidal	Not applicable
Vibrations (maximum frequency)	3000	Hz
Vibrations (amplitude)	20	g
Vibrations (duration)	12	hours
Shocks (type)	Sinusoidal	Not applicable
Shocks (amplitude)	50	g
Shocks (duration)	11	ms
Resonant frequency minimum	Not concerned	Hz
Static loads (minimum)	4	daN

Climatic performances		
Description	Data	Units
Maximum temperature of use	125	°C
Minimum temperature of use	-55	°C
Salt mist resistance	48	hours
Resistance to fluids	Fuel / Mineral and synthetic hydraulic fluid / Mineral and synthetic lubricant / Cleaning products / De icing fluid / Cooling fluid	Not applicable
Interfacial sealing	147	mb
Air leakage	Not concerned	cm ³ /hour
Immersion at low air pressure	147	mb
IP indice	Not concerned	Not applicable

	DECLARATION OF DESIGN AND PERFORMANCE	Reference DDP 001720 2XX 00
	<i>Push pull connector type 1720</i>	Page 3 / 3

Electrical performances		
Description	Data	Units
Insulation resistance	5000	MΩ
Voltage proof test	1500	V
Maximum intensity	7.5	A
Contact resistance	Not concerned	mΩ
Shell electrical continuity	Not concerned	mΩ


Optical performances		
Description	Data	Units
Insertion loss	Not concerned	dB
Return loss	Not concerned	dB

Fire behaviour	
In compliance with standard	ABD 0031 / EN 2591-317

I hereby declare on behalf of the supplier that the information contained in this declaration of design and performance (DDP) is correct.

Date : 10/08/19

Sign :



Company : Amphenol Air LB

Position held : Engineering Manager

Name : Jerome CHEVALIER

Date : 10/08/19

Sign :



Company : Amphenol Air LB

Position held : Quality Manager

Name : Vincent BEYRIES